

**Special features**

- Including 0.5 m connecting cable

| | |
|-----------------------------------|-----------------------------------------------|
| Housing Material | Stainless steel, Die-cast aluminium |
| Housing Color | Silver |
| Material of Lens | Glass |
| Protection Class | Protection class III/safety extra-low voltage |
| Operating Mode | Constant voltage |
| Rated Input | 17 W |
| Rated Input Voltage | 24 V/DC |
| Power Supply Unit incl. | No |
| Connection Cable Secondary | Yes |
| Secondary Connection | WEIPU plug 4-pole |
| Secondary Cable Length | 0.5 m |
| Dimmable | Yes |
| Control technology | Dimmable via optional controller |
| Motion Detector | No |

| | |
|-----------------------------------------|----------------------------------|
| Light Source | LED, Light source not changeable |
| Colour Consistency | 6 SDCM |
| Rated Luminous Flux | 510 lm |
| Luminous Efficiency | 30 lm/W |
| Rated Angle of Reflection | 30 Degree |
| Light Distribution | Symmetric |
| Distribution Characteristic 120° | DLS |

| | |
|------------------------------|--------|
| Light Exit Surfaces | 1 |
| Light characteristics | Direct |
| Light direction | Top |

| | |
|---------------------------|--------|
| Height | 38 mm |
| Diameter | 173 mm |
| Installation Depth | 50 mm |
| Cut Out Diameter | 150 mm |
| Product weight | 1200 g |

| | |
|----------------------------|--------------|
| Working Temperature | -20 to 40 °C |
| Storage Temperature | -10 to 60 °C |
| IP Protection Class | IP 67 |
| Load Force max. | 5 kN |
| Life Time L70 / B50 | 25000 h |
| Switching Cycles | 100000 |
| Power Consumption | 17 kWh/1000h |