



The timeless MEROPE demonstrates not only impressively high luminous flux and a low assembly height, it is also highly visually appealing thanks to its elegant outer aluminium ring – available in sandblasted white or black, brushed in silver or on-trend coffee. Available in the diameters 400 mm, 600 mm and 800 mm, the MEROPE can be integrated into very different environments even more flexibly.

#### Special features

- High luminous flux
- Light colour adjustable in 2 stages
- Low assembly height

In addition, the light colour can be adjusted in 2 stages, 3,000 K or 4,000 K.

<b>Housing Material</b>	Aluminium	<b>Switching Cycles</b>	20000
<b>Housing Color</b>	Silver	<b>Power Consumption</b>	30 kWh/1000h
<b>Housing Surface</b>	Brushed	<b>Energy Efficiency Class Lightsource</b>	This product contains a light source of energy efficiency class E.
<b>Material of Lens</b>	Acryl		
<b>Protection Class</b>	Protection class I/protective grounding		
<b>Rated Input</b>	30 W		
<b>Rated Input Voltage Frequency</b>	220-240 V/AC 50 / 60 Hz		
<b>Power Supply Unit incl.</b>	Yes		
<b>Connection Type</b>	Clamp		
<b>Dimmable</b>	Yes		
<b>Control technology</b>	Leading-edge dimmer, Trailing-edge dimmer		
<b>Motion Detector</b>	No		
<b>Light Source</b>	LED, Light source changeable TC		
<b>Color Temperature</b>	3000/4000 K		
<b>Colour Consistency</b>	6 SDCM		
<b>Colour Rendering Index (Ra)</b>	80		
<b>Rated Luminous Flux</b>	2100/2200 lm		
<b>Rated Luminous Flux 2</b>	2200 lm		
<b>Light Exit Surfaces</b>	1		
<b>Light characteristics</b>	Direct		
<b>Light direction</b>	Below		
<b>Height</b>	60 mm		
<b>Diameter</b>	380 mm		
<b>Working Temperature</b>	-10 to 45 °C		
<b>Storage Temperature</b>	-10 to 45 °C		
<b>IP Protection Class</b>	IP 20		
<b>Life Time L70 / B50</b>	30000 h		