

Connector - with TE screw terminals, for harsh applications



| Product description | |
|---------------------------|----------------|
| BALS-Prd.-Nr | 3152 |
| EAN | 4024941031523 |
| Product category | Connector TE |
| Current | 63A |
| Number of poles | 4p |
| Poles | 3P+PE |
| Position of earth contact | 7 h |
| Voltage | 480 up to 500V |

| Product description | |
|------------------------|---|
| Frequency | 50 and 60Hz |
| Protection degree | IP44 |
| Colour code | black RAL 9005 |
| Colour of appliance | Pusher grey RAL 7035, Collar black RAL 9005, Hinged lid black RAL 9005, Cable gland grey RAL 7035, Housing cover black RAL 9005 |
| Connection design | screw terminal as box terminal with Kontex-contact |
| Maximum conductor size | 16,0 qmm |
| Cable entry | Cable gland |
| Height | 252mm |
| Width | 97mm |
| Depth | 109mm |
| Material of enclosure | Polyamide |
| Contact | The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated |

| Additional technical properties | |
|---------------------------------|--|
| | For cable diameter from 16 up to max. 36 mm, Screwless housing connection, Multi-Grip cable gland with gasket, integrated cable clamp and additional water evacuation openings |

| Logistics data | |
|----------------|-----------------|
| Weight/pcs | 0.64 kg / Piece |
| Packaging | Bag |

| Logistics data | |
|----------------|---------------|
| Content amount | 1 ST |
| EAN | 4024941031523 |
| Length | 109 mm |
| Width | 97 mm |
| Height | 252 mm |
| Weight | 0.641 kg |
| Volume | 2,664.396 ccm |
| Packaging | Carton |
| Content amount | 5 ST |
| EAN | 4024941954938 |
| Length | 325 mm |
| Width | 217 mm |
| Height | 210 mm |
| Weight | 3.406 kg |
| Volume | 13,588.4 ccm |



3 MB 107

| Ampere | 63 | 63 | 63 | | | | |
|----------------------------|-------|-------|-------|--|--|--|--|
| Polzahl | 3 | 4 | 5 | | | | |
| a ø | 95,0 | 95,0 | 95,0 | | | | |
| b | 251,0 | 251,0 | 251,0 | | | | |
| c | 109,0 | 109,0 | 109,0 | | | | |
| d ø | 36,0 | 36,0 | 36,0 | | | | |
| Leiter mm ² min | 6 | 6 | 6 | | | | |
| Leiter mm ² max | 16 | 16 | 16 | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |