

**Special features**

- Including 10 m connecting cable with WEIPU IP67 plug

Housing Material	Stainless steel	Cut Out Diameter	59 mm
Housing Color	Silver	Product weight	810 g
Material of Lens	Glass	Working Temperature	-20 to 50 °C
Protection Class	Protection class III/safety extra-low voltage	Storage Temperature	-10 to 60 °C
Operating Mode	Constant voltage	IP Protection Class	IP 68/max. 2 m
Rated Input	3 W	Life Time L70 / B50	25000 h
Rated Input Voltage	24 V/DC	Switching Cycles	100000
Power Supply Unit incl.	No	Power Consumption	3 kWh/1000h
Connection Cable Secondary	Yes	Energy Efficiency Class	G
Secondary Connection	WEIPU plug 2-pole		
Secondary Cable Length	10 m		
Dimmable	Yes		
Control technology	Dimmable via optional controller		
Motion Detector	No		
Light Source	LED, Light source not changeable		
Color Temperature	3000 K		
Colour Consistency	6 SDCM		
Colour Rendering Index (Ra)	80		
Rated Luminous Flux	105 lm		
Luminous Efficiency	35 lm/W		
Rated Angle of Reflection	45 Degree		
Rated Angle of Reflection 2	35 Degree		
Light Distribution	Asymetric		
Distribution Characteristic 120°	DLS		
Light Exit Surfaces	1		
Light characteristics	Direct		
Light direction	Top		
Height	73 mm		
Diameter	68.5 mm		
Installation Depth	135 mm		