




Housing Material	Aluminium, Stainless steel	Length	625 mm
Housing Color	White	Width	625 mm
Functions	Leuchte kann mit Gleichstrom aus einer Zentralbatterie eines Notstromsystems betrieben werden., Korridorfunktion mit extern verbauten DALI-Sensor.	Height	48 mm
		Working Temperature	-10 to 40 °C
		Storage Temperature	-10 to 40 °C
		IP Protection Class	IP 40
Protection Class	Protection class I/ protective grounding	Life Time L70 / B50	50000 h
Protection Class Lamp	Protection class III/ safety extra-low voltage	Life Time L80 / B20	50000 h
Rated Input	35 W	Switching Cycles	100000
Rated Power Consumption Standby	0.5 W	EEL	F
Rated Power Consumption Network Standby	0.5 W		
Rated Input Voltage Frequency	198-264 V/AC 50 / 60 Hz		
Power Supply Unit incl.	Yes		
Dimmable	Yes		
Control	DALI 2 / DT6, Push-Dim, Intelli Push-Dim		
Motion Detector	No		
Voltage range emergency lighting	176-280 V/DC		
EOFI	95 %		
Light Source	LED, Light source not changeable		
Color Temperature	3000/4000 K		
Colour Consistency	3 SDCM		
Colour Rendering Index (Ra)	90		
Rated Luminous Flux	4400/4600 lm		
Rated Angle of Reflection	90 Degree		
UGR	19		