



Special features

- Suitable for workplaces with screens
- Very low glare value
- Low housing depth
- Optionally available as pendant lamp

Housing Material	Aluminium
Housing Color	White
Material of Lens	PMMA
Protection Class	Protection class III/safety extra-low voltage
Operating Mode	Constant current
Rated Input	36 W
Rated Input Voltage	33-38 V/DC
Rated Current	1050 mA
Power Supply Unit incl.	No
Dimmable	Yes
Control technology	Dimmable via optional power supply unit
Motion Detector	No

IP Protection Class	IP 40
IK Protection Class	IK03
Life Time L70 / B50	40000 h
Switching Cycles	100000
Power Consumption	36 kWh/1000h
Energy Efficiency Class	F

Light Source	LED, Light source not changeable
Color Temperature	4000 K
Colour Consistency	6 SDCM
Colour Rendering Index (Ra)	90
Rated Luminous Flux	4200 lm
Luminous Efficiency	116.7 lm/W
Rated Angle of Reflection	90 Degree
UGR	19
Distribution Characteristic 120°	DLS

Light Exit Surfaces	1
Light characteristics	Direct
Light direction	Below

Length	620 mm
Width	620 mm
Height	9 mm

Working Temperature	-20 to 45 °C
Storage Temperature	-40 to 80 °C